

SINCE 1925

KEYSTONE

SAFETY ↔ CLEANROOM PRODUCTS

1422A TYVEK® AUTOCLAVABLE STOPPER BOWL COVERS WITH WINDOW



Save time by using the stopper bowl cover with windows instead of wrapping with sheets of material and autoclave tape. When used in conjunction with a secondary Tyvek® Bag, it creates an effective wrapping system. After the outer bag is removed, this stopper bowl cover should remain in place, providing protection from microbial and particulate contamination while the remaining set-up activities are performed.

TYPICAL APPLICATION & CHARACTERISTICS:

- Steam sterilization indicator
- Clear integrated window allows operator to verify the inside of the stopper bowl is dry before use
- Lint-free
- Autoclavable at 121°C - 125°C
- Hydrophobic
- Resists tearing and punctures
- Manufactured and packaged in ISO certified Cleanroom
- Conveniently packaged: 1 per heat-sealed labeled poly bag
- Certificates of Conformance sent with shipment
- Made in USA

WINDOW MATERIAL

PHYSICAL PROPERTIES	
Material – Extruded composite of polyester and a high temperature sealant. Gauge (ASTM F2251)	2.6 mil 67 micron
Yield	11,080 in ² /lb
THERMAL PROPERTIES	
For best results do not exceed steam sterilization temperatures of 257°F / 125°C.	

SINCE 1925

KEYSTONE

SAFETY ↔ CLEANROOM PRODUCTS

1422A TYVEK® STOPPER BOWL COVERS WITH WINDOW



TYVEK MATERIAL SPECIFICATIONS:

PROPERTY	UNITS	TEST METHOD	TYPICAL VALUES 1422A TYVEK®
Basis Weight	g/m ²	EN ISO 536	41
Total Thickness	μ	EN 20534	130
Air Permeability	s	ISO 5636-5	20
Water Vapor Permeability	G/M ² /24 HR	ASTM 398	1700
Hydrostatic Head	cm H ₂ O	ISO 811	120
Trapezoidal Tear MD/CD	N	ISO 9073-4	26.1/30.6
Linting Propensity	Rating	BS 6909 (Shirley Method 21)	Pass Rating: Excellent
Burst Resistance	kPa	ISO 2960 (50 cm ²)	108
Puncture Resistance	N	EN 863	10.8
Melting Point	C°		135

KEYSTONE PART NUMBER	SIZE CHART
BWLT2A20-WW	Fits 27.94 cm to 40.64 cm Diameter
BWLT2A24-WW	Fits 30.48 cm to 50.8 cm Diameter
BWLT2A26-WW	Fits 35.56 cm to 55.88 cm Diameter
BWLT2A30-WW	Fits 50.8 cm to 66.04 cm Diameter
BWLT2A36-WW	Fits 66.04 cm to 76.2 cm Diameter
BWLT2A42-WW	Fits 71.12 cm to 88.9 cm Diameter
BWLT2A46-WW	Fits 76.2 cm to 96.52 cm Diameter
BWLT2A48-WW	Fits 76.2 cm to 101.6 cm Diameter
BWLT2A54-WW	Fits 88.9 cm to 114.3 cm Diameter
BWLT2A60-WW	Fits 101.6 cm to 127 cm Diameter
BWLT2A72-WW	Fits 127 cm to 152.4 cm Diameter