

SINCE 1925

KEYSTONE

SAFETY ↔ CLEANROOM PRODUCTS

1422A TYVEK® AUTOCLAVE BAG WITH STEAM INDICATOR



TYPICAL APPLICATION & CHARACTERISTICS:

Recommended for Steam Sterilization of Pharmaceutical Production Equipment

- Cost Effective
- Tyvek® on both sides for maximum steam penetration during sterilization
- Minimizes the use of autoclave tape
- Fast and consistent for equipment preparation area
- Creates strong seals when heat sealed
- Hydrophobic
- Resists tearing and punctures
- Superior microbial barrier
- Lint-Free
- Manufactured and packaged in ISO certified cleanrooms
- Certificates of Conformance sent with all shipments
- Made in USA

MATERIAL SPECIFICATIONS:

PROPERTY	UNITS	TEST METHOD	TYPICAL VALUES 1422A TYVEK®
Seal Strength	N/mm	F-88	>.78
Basis Weight	g/m ²	EN ISO 536	41
Total Thickness	μ	EN 20534	130
Air Permeability	s	ISO 5636-5	20
Water Vapor Permeability	G/M ² /24 HR	ASTM 398	1700
Hydrostatic Head	cm h ₂ o	ISO 811	120
Trapezoidal Tear MD/CD	N	ISO 9073-4	26.1/30.6
Linting Propensity	Rating	BS 6909 (Shirley Method 21)	Pass Rating: Excellent
Burst Resistance	kPa	ISO 2960 (50 cm ²)	108
Puncture Resistance	N	EN 863	10.8
Melting Point	c°		135

SINCE 1925

KEYSTONE

SAFETY ↔ CLEANROOM PRODUCTS

1422A TYVEK® AUTOCLAVE BAG WITH STEAM INDICATOR



KEYSTONE PART NUMBER	DIMENSIONS (cm)	KEYSTONE PART NUMBER	DIMENSIONS (cm)
BGT2A0205	5.08 x 12.7	BGT2A1624	40.64 x 60.96
BGT2A0404	10.16 x 10.16	BGT2A1830	45.72 x 76.2
BGT2A0409	10.16 x 22.86	BGT2A2020	50.8 x 50.8
BGT2A0416	10.16 x 40.64	BGT2A2024	50.8 x 60.96
BGT2A0820	20.32 x 50.8	BGT2A2030	50.8 x 76.2
BGT2A09-512	24.13 x 30.48	BGT2A2040	50.8 x 101.6
BGT2A1015	25.4 x 38.1	BGT2A2224	55.88 x 60.96
BGT2A1020	25.4 x 50.8	BGT2A2424	60.96 x 60.96
BGT2A1212	30.48 x 30.48	BGT2A2436	60.96 x 91.44
BGT2A1216	30.48 x 40.64	BGT2A2448	60.96 x 121.92
BGT2A1218	30.48 x 45.72	BGT2A2844	71.12 x 111.76
BGT2A1234	30.48 x 86.36	BGT2A3036	76.2 x 91.44
BGT2A1240	30.48 x 101.6	BGT2A3636	91.44 x 91.44
BGT2A1246	30.48 x 116.84	BGT2A3648	91.44 x 121.92
BGT2A1248	30.48 x 121.92	BGT2A3660	91.44 x 152.4
BGT2A1424	35.56 x 60.96	BGT2A4848	121.92 x 121.92