

SINCE 1925

KEYSTONE

SAFETY ↔ CLEANROOM PRODUCTS

1422A TYVEK® STEAM STERILIZATION WRAPPER



TYPICAL APPLICATION & CHARACTERISTICS:

- Designed for steam sterilization
- Recommended for use in conjunction with a secondary Tyvek® sterilization pouch
- Hydrophobic
- Excellent Microbial Barrier
- Resists tearing and punctures
- Lint-free
- Manufactured and packaged in ISO certified cleanrooms
- Certificates of Conformance sent with all shipments
- Made in USA

MATERIAL SPECIFICATIONS:

PROPERTY	UNITS	TEST METHOD	TYPICAL VALUES 1422A TYVEK®
Basis Weight	g/m ²	EN ISO 536	41
Total Thickness	μ	EN 20534	130
Air Permeability	s	ISO 5636-5	20
Water Vapor Permeability	G/M ² /24 HR	ASTM 398	1700
Hydrostatic Head	cm h ₂ O	ISO 811	120
Trapezoidal Tear MD/CD	N	ISO 9073-4	26.1/30.6
Linting Propensity	Rating	BS 6909 (Shirley Method 21)	Pass Rating: Excellent
Burst Resistance	kPa	ISO 2960 (50 cm ²)	108
Puncture Resistance	N	En 863	10.8
Melting Point	C°		135

SINCE 1925

KEYSTONE

SAFETY ↔ CLEANROOM PRODUCTS

1422A TYVEK® STEAM STERILIZATION WRAPPER



KEYSTONE PART NUMBER	DIMENSIONS (cm)	KEYSTONE PART NUMBER	DIMENSIONS (cm)
T2ASHEET0303	7.62 x 7.62	T2ASHEET2020	50.8 x 50.8
T2ASHEET0404	10.16 x 10.16	T2ASHEET2424	60.96 x 60.96
T2ASHEET0606	15.24 x 15.24	T2ASHEET3030	76.2 x 76.2
T2ASHEET07-507-5	19.05 x 19.05	T2ASHEET4040	101.6 x 101.6
T2ASHEET0909	22.86 x 22.86	T2ASHEET4080	101.6 x 203.2
T2ASHEET0911	22.86 x 27.94	T2ASHEET6060	152.4 x 152.4
T2ASHEET1212	30.48 x 30.48	T2ASHEET60140	152.4 x 355.6
T2ASHEET1515	38.1 x 38.1	T2ASHEET7272	182.88 x 182.88
T2ASHEET1818	45.72 x 45.72	T2ASHEET8494	213.36 x 238.76