

SINCE 1925

KEYSTONE

SAFETY ↔ CLEANROOM PRODUCTS

BLUE HEAVY DUTY AUTOCLAVABLE SMS MUFF COVER



Heavy Duty SMS Muffs eliminate the need for cutting sheets of sterilization wrapping materials and securing them with autoclave tape and rubber bands. This cost effective, time saving approach standardizes the equipment preparation process, minimizes particulate generation, while also ensuring good aseptic technique upon removal after sterilization.

TYPICAL APPLICATION & CHARACTERISTICS:

- Eliminates autoclave tape residue
- SMS has excellent microbial barrier properties
- Can be sterilized in 135° autoclave cycles
- Hydrophobic
- Resists tearing and punctures
- Lint-free
- Manufactured and packaged in ISO certified cleanrooms
- Conveniently packaged: 100 Muffs per heat-sealed and labeled poly bag
- Certificates of Conformance sent with all shipments
- Made in USA

MATERIAL SPECIFICATIONS:

PROPERTY	SPECIFICATION	UNIT
Basis Weight	50	Gm/m2
Grab Strength (CD)	20	lbs
Tear Strength (MD)	7.5	lbs
Mullen Burst Strength (Gross)	34	psi
Air Permeability	50	cfm
Hydrohead	55	mbar

SINCE 1925

KEYSTONE

SAFETY ↔ CLEANROOM PRODUCTS

BLUE HEAVY DUTY AUTOCLAVABLE SMS MUFF COVER



Keystone CRP Part No.	Size
MFKCRP300-03	Fits Openings with Diameters 1.3 cm to 2.5 cm
MFKCRP300-04	Fits Openings with Diameters 2.5 cm to 4.4 cm
MFKCRP300-05	Fits Openings with Diameters 4.4 cm to 6.4 cm
MFKCRP300-06	Fits Openings with Diameters 5 cm to 7 cm
MFKCRP300-07	Fits Openings with Diameters 6.4 cm to 10.2 cm
MFKCRP300-08	Fits Openings with Diameters 8.9 cm to 12 cm
MFKCRP300-09	Fits Openings with Diameters 10.2 cm to 14 cm
MFKCRP300-12	Fits Openings with Diameters 14 cm to 20.3 cm
MFKCRP300-16	Fits Openings with Diameters 20.3 cm to 30.5 cm
MFKCRP300-18	Fits Openings with Diameters 25.4 cm to 35.6 cm