

SINCE 1925

KEYSTONE

SAFETY ↔ CLEANROOM PRODUCTS

SELF-SEALING 1422A TYVEK® AUTOCLAVE BAG WITH STEAM INDICATOR



TYPICAL APPLICATION & CHARACTERISTICS:

- Eliminate the need for autoclave tape
- Eliminate the need for heat sealer validation
- Recommended for steam sterilization of pharmaceutical production equipment
- Cost-effective
- Tyvek® on both sides for maximum penetration during sterilization
- Fast and consistent for equipment preparation area
- Hydrophobic
- Resists tearing and punctures
- Superior microbial barrier
- Lint-Free
- Manufactured and packaged in ISO certified Cleanroom
- Certificates of Conformance sent with all shipments
- Made in USA

MATERIAL SPECIFICATIONS:

PROPERTY	UNITS	TEST METHOD	TYPICAL VALUES 1422A TYVEK®
Seal Strength	N/mm	F-88	>.78
Basis Weight	g/m2	EN ISO 536	41
Total Thickness	μ	EN 20534	130
Air Permeability	s	ISO 5636-5	20
Water Vapor Permeability	G/M2/24 HR	ASTM 398	1700
Hydrostatic Head	cm h2o	ISO 811	120
Trapezoidal Tear MD/CD	N	ISO 9073-4	26.1/30.6
Linting Propensity	Rating	BS 6909 (Shirley Method 21)	Pass Rating: Excellent
Burst Resistance	kPa	ISO 2960 (50 cm2)	108
Puncture Resistance	N	EN 863	10.8
Melting Point	c°		135

SINCE 1925

KEYSTONE

SAFETY ↔ CLEANROOM PRODUCTS

SELF-SEALING 1422A TYVEK® AUTOCLAVE BAG WITH STEAM INDICATOR



KEYSTONE PART NUMBER	DIMENSIONS (cm)	KEYSTONE PART NUMBER	DIMENSIONS (cm)
BGT2A0205SS	5.08 x 12.7	BGT2A1830SS	45.72 x 76.2
BGT2A0404SS	10.16 x 10.16	BGT2A2020SS	50.8 x 50.8
BGT2A0409SS	10.16 x 22.86	BGT2A2024SS	50.8 x 60.96
BGT2A0416SS	10.16 x 40.64	BGT2A2030SS	50.8 x 76.2
BGT2A0820SS	20.32 x 50.8	BGT2A2040SS	50.8 x 101.6
BGT2A09-512SS	24.13 x 30.48	BGT2A2224SS	55.88 x 60.96
BGT2A1015SS	25.4 x 38.1	BGT2A2424SS	60.96 x 60.96
BGT2A1020SS	25.4 x 50.8	BGT2A2436SS	60.96 x 91.44
BGT2A1212SS	30.48 x 30.48	BGT2A2448SS	60.96 x 121.92
BGT2A1216SS	30.48 x 40.64	BGT2A2844SS	71.12 x 111.76
BGT2A1218SS	30.48 x 45.72	BGT2A3036SS	76.2 x 91.44
BGT2A1234SS	30.48 x 86.36	BGT2A3636SS	91.44 x 91.44
BGT2A1240SS	30.48 x 101.6	BGT2A3648SS	91.44 x 121.92
BGT2A1246SS	30.48 x 116.84	BGT2A3660SS	91.44 x 152.4
BGT2A1248SS	30.48 x 121.92	BGT2A4848SS	121.92 x 121.92
BGT2A1624SS	40.64 x 60.96		